

UL Style NO. Reference Chart

Style NO. UL	Material	Rated Temperature	Rated Voltage	Style NO. UL	Material	Rated Temperature	Rated Voltage
Single-conductor, thermoplastic insulation							
UL 1007	PVC	80°C	300Vac	UL 1015	PVC	80, 90, 105°C	600Vac, 750Vdc
UL 1028	PVC	105°C	600Vac	UL 1061	SRPVC	80°C	300Vac
UL 1283	PVC	105°C	600Vac	UL 1330	FEP	200°C	600Vac
UL 1332	FEP	200°C	300Vac	UL 1430	XLPVC	105°C	300Vac
UL 1431	XLPVC	105°C	600Vac	UL 1569	PVC	80, 90, 105°C	300Vac
UL 1592	FEP	200°C	300Vac	UL 1617	PVC	105°C	600Vac
UL 1672	PVC	105°C	300Vac	UL 10138	PE	80°C	300Vac
UL 10152	PP	80°C	300Vac	UL 10272	PVC	80°C	150Vac
UL 10737	PUR	80°C	300Vac				
Multiple-conductor, thermoplastic insulation							
UL 2092	PVC	60°C	300Vac	UL 2095	PVC	80°C	300Vac
UL 2103	PVC	105°C	300Vac	UL 2464	PVC	80°C	300Vac
UL 2481	PVC	105°C	300Vac	UL 2493	PVC	60°C	300Vac
UL 2517	PVC	105°C	300Vac	UL 2597	PVC	105°C	Voltage not specified
UL 2598	PVC	60°C	300Vac	UL 2835	PVC	60°C	30Vac
UL 2919	PVC	80°C	30Vac	UL 2990	PVC	80°C	30Vac
UL 20276	PVC	60°C	30Vac	UL 20280	PUR	80°C	300Vac
UL 20549	TPU	80°C	300Vac				
Single-conductor, thermoset insulation							
UL 3132	SR-SILICONE	105°C	300Vac	UL 3135	SR-SILICONE	200°C	600Vac
UL 3173	XLPE	125°C	600Vac	UL 3182	XLPE	125°C	600Vac
UL 3212	SR-SILICONE	150°C	600Vac	UL 3265	XLPE	125°C	150Vac
UL 3266	XLPE	125°C	300Vac	UL 3271	XLPE	125°C	600Vac
UL 3289	XLPE or XLPO	150°C	600Vac	UL 3321	XLPE	150°C	600Vac
UL 3512	SR-SILIXONE	200°C	600Vac				